



SolarEdge Power Optimizer

Module Add-On

OP250-LV / OP300-MV / OP400-MV / OP400-EV

POWER OPTIMIZERS



PV power optimization at the module-level

- High efficiency with module-level MPPT, for maximized system energy production and revenue, and fast project ROI only
- Superior efficiency (99.5%)
- Mitigates all types of modules mismatch-loss, from manufacturing tolerance to partial shading
- Flexible system design for maximum space utilization
- Next generation maintenance with module level monitoring
- Module-level voltage shutdown for installer and firefighter safety



SolarEdge Power Optimizer Module Add-On

OP250-LV / OP300-MV / OP400-MV / OP400-EV

	OP250-LV	OP300-MV	OP400-MV	OP400-EV	
INPUT					
Rated Input DC Power*	250	300	400	400	W
Absolute Maximum Input Voltage (Voc)	55	75	75	125	Vdc
MPPT Operating Range	5 - 55	5 - 75	5 - 75	15 - 125	Vdc
Maximum Continuous Input Current (Isc)	10	10	10	7	Adc
Maximum Efficiency					99.5 %
Weighted Efficiency					98.8 %
Overvoltage Category					II
OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING INVERTER)					
Maximum Output Current					15 Adc
Operating Output Voltage					5 - 60 Vdc
OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM INVERTER OR INVERTER OFF)					
Safety Output Voltage per Power Optimizer					1 Vdc
STANDARD COMPLIANCE					
EMC					FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3
Safety					IEC62109-1 (class II safety), UL1741
Material					UL-94 (5-VA), UV Resistant
RoHS					Yes
INSTALLATION SPECIFICATIONS					
Maximum Allowed System Voltage					1000 Vdc
Dimensions (W x L x H)					143 x 210 x 45 / 5.63 x 8.26 x 1.75 mm / in
Weight					450 / 1.0 gr / lb
Input Connector					MC4 / Tyco / H+S / Amphenol
Output Wire Type					6mm ² ; MC4
Output Wire Length	0.95 / 3.0			1.2 / 3.9	1.6 / 5.25 m / ft
Operating Temperature Range					-40 - +65 / -40 - +150 °C / °F
Protection Rating					IP65 / NEMA4
Relative Humidity					0 - 100 %

* Rated STC power of the module. Module of up to +5% power tolerance allowed.

PV SYSTEM DESIGN USING A SOLAREEDGE INVERTER	SINGLE PHASE		THREE PHASE	
	Minimum String Length (Power Optimizers)	8		16
Maximum String Length (Power Optimizers)	25		50	
Maximum Power per String	5250		11250	W
Parallel Strings of Different Lengths or Orientations	Yes			

